

CVO-2-HT VACUUM OVEN

Capacity	1.67 cu.ft. (47.2 liters)
Interior Dimensions (W x D x H)	12" x 20" x 12" 304 x 508 x 304 mm
Exterior Dimensions (W x D x H)	20.5" x 31.0" x 26.3" 521 x 788 x 667 mm
Unit Weight	179 lb (81 kg)
Shipping Weight	218 lb (99 kg)
Shelves	3 standard, 3 total
Maximum Weight Per Shelf	35 lb / 15.8 kg
Permitted Total Load	105 lb / 47.6 kg
Standard Door Gasket	Silicone Standard
Access Port	1" vacuum port (KF25)
Controls	Watlow EZ-ZONE
Warranty	2 Year Limited Warranty
Interior Construction	300 series stainless steel
Exterior Construction	20 gauge steel, powder coated
Wall Clearance, Each Side	6.0" (152 mm)
Wall Clearance, Rear	12.0" (305 mm)
Vertical Clearance	12.0" (305 mm)
Electrical, 50/60Hz, AC, 1Ø	
Voltage	110V-120V
Full Load Amps	10
Nominal Power (watts @150°C)	662
NEMA Plug Supplied	5-15P
Energy Consumption (kWh/day)	
At 80°C	12.8
At 150°C	15.4
At 220°C	24.4
Temperature Range 10°C above ambient to 220°C	
Heat-Up Time— Minutes to 80°C	70
Heat-Up Time — Minutes to 150°C	120
Heat-Up Time — Minutes to 220°C	175
Temperature Uniformity	+/- 6% of Set Point
Temperature Stability	+/- 0.2°C @ 150°C
Operational Vacuum Range	-3.0 to -29.9 InHg
Vacuum Display Range	0-29.9 InHg
Safety Certifications	UL 61010-1, EN 61010-1, CSA 61010-1, CE

We reserve the right to change specifications at any time



6725 NE Evergreen PKWY, Suite 106
Hillsboro, Oregon 97124
503.847.9047
www.cascadesciences.com

